

PEN TYPE CONDUCTIVITY/TDS METER AZ-8361



FEATURE

- WATER PROOF MEMBRANE KEYPAD.
- LOW COST DESIGN WITH HIGH ACCURACY.
- QUICK RESPONSE AND EASY TO CALIBRATE.
- ADJUSTABLE TDS FACTOR FROM 0.4 TO 1.0 AUTO POWER OFF.

- HOLD CURRENT READING.
- IP65 Waterproof housing.
- Dual display with ATC.
- Data hold to freeze readings.
- Pen size, easy to fit in pocket.
- Low battery indicator. Auto power off disable. C/F unit switchable.
- Replace with 4pcs LR44 batteries.
- Multi points calibration.
- One touch only for calibration.

SPECIFICATION

Conductivity/TDS range:	0~1999 uS / 0~1999 ppm or 0~19.99 mS / 0~19.99 ppt
Resolution:	1 uS or 0.01mS or 0.01ppt
Accuracy:	1% Full Scale 1 dgt
Calibration standard range:	(0.2~1) * full scale
Operating temperature:	0~50°C
Temperature compensation:	0~50°C
Temperature coefficient:	0~4.0% per degree C
Normalization temperature:	20 or 25°C
Power requirements:	4x1.5V batteries (Type A76 or LR44)
Calibration:	2 point (Calibration range is \pm 40% of factory default parameter)
Dimension (H x W x T):	165 x 35 x 32mm.
Standard packing included::	Meter, manual, batteries, plain box.