

**DIGITAL SLING PSYCHROMETER**  
**Model : AZ-8706**



**Feature:**

- Micro processor-based design. A must device for HVAC engineers
- No whirling the meter or refer to the chart need, easy to get Wet Bulb / Dry Bulb and Dew Point temperature quickly! (Model 8706)
- °C or °F unit switchable, battery low indication, self-calibration available for longer life by salt solution
- Fast response, high accuracy. Data Hold freezes the reading. Auto power off and disablement
- Display resolution 0.1°C or 0.1 °F of reading
- Condensation will not affect meters' accuracy
- Humidity sensor: Rotronic electronic capacitance type

**EZTECH**  
**EZTECH**  
**ESLECH** **Instruments**

*The Art Of Measurements*

[www.WorldTesters.com](http://www.WorldTesters.com)

[sales@eztech-usa.com](mailto:sales@eztech-usa.com)

## Specification

<b>Temp. range</b>	-20~+50°C (-4~+122°F)	<b>Extension cable length</b>	116cm (with phone jack 2.5mm)
<b>RH% range</b>	0~100%RH	<b>Probe(with handle)</b>	20cm (approx)
<b>Wet blub range</b>	-21.6~50.0°C (-6.9~122°F)	<b>Package</b>	Gift box, Battery, Manual.
<b>Dew point range</b>	-78.7~50.0°C (-109.7~122°F)	<b>Power</b>	2x1.5V AAA battery
<b>External temp. range</b>	-20~70°C (-4~158°F)	<b>Optional accessory</b>	External temp. probe VZ87P6 AZ
<b>Accuracy</b>	RH%: ±3% at 25°C		Humidity calibration salt solution (HR33, HR75)
	Temperature: ±1°F (0.6°C)	<b>Response time</b>	60 seconds typical
<b>Pocket size</b>	24.7 (H) x 48.4 (W) x 178.5mm (L)		