

60° Gloss Meter

Model: GT60Plus



Feature:

- Small and light, real easy to be carried and used.
- One 1.5 mignon alkaline Battery can be used for almost 60 hours and 10000 reading.
- High stability
- Long-term stable light source needs no replacing forever.
- Quartz crystal standard board, no excursion.
- Designed and manufactured according to international standards ISO2813,ASTMD523,DIN67530 GB9754,GB9966,GB/T3891 The technical parameters up to JJG696-2002.

EZTECH
EZTECH Instruments
ESLECH

The Art Of Measurements

www.WorldTesters.com

sales@eztech-usa.com

Applications:

1. Measurement of Paint and Dope surface gloss on Car, Electronic appliance and Musical Instrument industry.
2. Measurement of floor board, marble, granite and ceramic tile gloss on architecture, decoration industry.
3. Measurement of printing ink and paper on Printing and Casing industry.
4. Measurement of the others need to be measured.
5. Hard drawn aluminum alloys

Geometry	60°
Measuring range (GU)	L: 0 to 199.9 H: 0 to 1999
Stability (GU/30Min)	<±0.4
Accuracy	L: < ±1.2 GU H: <1.5%
Power supply	1 x 1.5V AA alkaline battery
Measurement opening dimension (mm)	10x20
Windows Size (mm)	14x28
Working temperature (°C)	0 to 40
Relative humidity	<85%
Dimension (mm)	114x32x64
Weight (g)	300
Application	Metal, Dope, Plating layer
International Standards	ISO2813, ASTM D523, ISO7668
GB Standards	GB9754